



# Water Coolers



## ON-A-WALL

## P8M, PLF8MH, P14M, PL14MH, PM

### Suggested Specification

Cabinet finish shall be Sandstone powder coat paint on galvanized steel or brushed stainless steel. Cooling system shall use R-134a refrigerant. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives.

### Models

**P8M** delivers 8 gph of chilled drinking water

**PLF8MH** is a Hot 'N Cold and serves 45 cups of piping hot water per hour, plus 8 gph of chilled water.

**P14M** delivers 14 gph of chilled drinking water.

**PLF14FM** is a Hot 'N Cold and serves 45 cups of piping hot water per hour, plus 8 gph of chilled water.

**PM** is a non-refrigerated fountain.

### Standard Features

- > Waterways Are Lead-Free In Materials & Construction
- > Dial-A-Drink® Bubbler
- > Stainless Steel Top
- > Welded Heavy-Gauge Steel Frame
- > High-Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Limited 5-year Warranty

### Finishes

- > Standard Cabinet Finish: Sandstone powder coated paint on Galvanized Steel.
- > Optional finishes at extra cost: Stainless Steel, Regency Bronze, Powder coated Paint.



Components in these water coolers are lead free as defined by the Safe Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

### Accessories

- > Trim Bezel to conceal wall surface discoloration when cooler is installed as a replacement.
- > Glass Fillers: Push handle (029603-004)
- > Glass Fillers: Push back (029603-005)
- > Glass Fillers: Push down (029603-006)
- > Kit 029137-002 is required for Field Installation for the above glass fillers (Except Models PLF8MH and Regency Bronze finish.)

### Installation

- > Prior to roughing-in consult with local, state, and federal codes for proper mounting height.
- > Shipped with complete instructions and wall mounting bracket.
- > Removable panels provide easy access for installation.

**Limited 5-Year Warranty** (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty:** One year on the sealed refrigeration system and most component parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Models covered by this specification complies with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives.



NSF certified P8M only

Model	50° F Drinking Water 90° F Ambient Air Temp*				115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler	Hot'N Cold™ Model	Compr. HP	Full Load Amps	Rated Watts			
P8M	8.0	8.0	No	No	1/5	4.3	320	Yes	Yes	73 Lbs.
PLF8MH †	8.0	8.0	No	Yes	1/5	8.9	820	No	Yes	77 Lbs.
P14M**	14.0	7.8	Yes	No	1/5	4.6	320	Yes	Yes	76 Lbs.
PLF14MH †	14.0	7.8	Yes	Yes	1/5	8.9	820	No	Yes	79 Lbs.
PM									Yes	35 Lbs.

\*Industry Standard Rating Condition 80° F inlet water temperature. †Hot 'N Cold Model delivers 45 six-ounce of hot water per hour in addition to cold water.

\*\*Special export models available, operable on 220-240 volts, 50/60 Hz.

Specifications subject to change without notice

