



Water Coolers

ANTIMICROBIAL RADII™ BI-LEVEL MODULAR

M8CR

Suggested Specification

Shall deliver 8.0 gph of 50° F degree water at 90° F ambient and 80° F inlet water. Model M8CR shall include push pads to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Fountains shall be designed to eliminate splashing and standing water. Bubbler shall have a flexible guard and operate between 20 and 120 psi. As a standard feature, the bubblers and push pads contain an antimicrobial silver additive (AlphaSan®) that inhibits the growth of bacteria, fungus, mold and mildew. Chiller unit shall use R-134a refrigerant. Shall be listed by Underwriters' Laboratories certified by Canadian Standards Association. Shall comply with ANSI A117.1 and ADA. Shall comply with the Safe Drinking Water Act and Lead Contamination Control Act. Shall comply with ANSI/NSF 61.

RADII™ Modular Bi-Level Water Cooler meets the needs of the physically challenged and the able bodied.

Model

M8CR A light press of the push pad activates the water flow.

Standard Features

- > AlphaSan® antimicrobial additive in bubblers and push pads
- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Flexible bubbler guard
- > Waterways are Lead-Free in Materials & Construction
- > Brushed Stainless Steel Finish
- > Refrigerant R-134a
- > Heavy duty galvanized steel wall mounting frame
- > High efficiency cooling system
- > Limited 5-Year Warranty

Finishes

Standard Finish: Stainless Steel

Optional Finish (at additional cost) Regency Bronze

Installation

- > Prior to roughing-in, consult local, state and federal codes for proper mounting height.
- > Wall mounting frame is furnished for easy installation

Options (at additional cost)

- > Stainless steel bubbler



ADA Compliant when installed in an alcove or with right and left wing walls.



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on the sealed refrigeration system and most components parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each cooler; sample copy available upon request.

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives.



Certified to
NSF/ANSI 61/Section 9

Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot'N Cold™ Model	115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Cooling Capacity GPH	Base Rate GPH	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
M8CR	8.0	8.0	No	No	1/5	4.6	340	No	Yes	161 Lbs.

*Industry Standard Rating Condition 80° F inlet water temperature.
Specifications subject to change without notice

